



# The Water O<sub>3</sub>zonator

Model WOZ5 Manual

## CONTENTS

WELCOME TO SOTA .....	2
BEFORE USING .....	2
LEARN MORE .....	2
COMPLETE UNIT INCLUDES.....	2
DO NOT USE.....	3
CAUTIONS .....	3
SUMMARY OF LIGHTS .....	3
HOW TO USE THE WATER OZONATOR .....	3
Typical Use.....	5
STERILIZING WATER.....	5
WATER DISINFECTION TESTS .....	6
TIMING TO SATURATE WITH OZONE .....	6
OXIDATION REDUCTION POTENTIAL (ORP) .....	6
ELECTRICAL SPECIFICATIONS .....	6
TROUBLESHOOTING.....	7
COUNTRIES THAT PARTICIPATE IN MANUFACTURING.....	7
REPLACEMENT ACCESSORIES.....	7
WARRANTY.....	7
REPAIRS.....	7

## WELCOME TO SOTA

Thank you for allowing us to be a part of your wellness team.

The Water Ozonator is a consumer product designed to be used as part of a Wellness Lifestyle. A commitment to healthy lifestyle choices is an important factor in the journey to Wellness.

The SOTA Water Ozonator produces freshly-ozonated water. The fresh taste and extra oxygen are an energizing way to hydrate your body.

The Water Ozonator is designed to be used independently, but can also be used together with any of the SOTA Products.

With proper care, your Water Ozonator should provide you many years of trouble-free use.

Please understand that results will vary.

## BEFORE USING

Please read the manual thoroughly before using your Water Ozonator.

We've made every effort to ensure the information in your manual is up-to-date at the time of printing ... since that time however, new information may have become available. For the most up-to-date manual, please visit our website [www.sota.com/manuals](http://www.sota.com/manuals).

## LEARN MORE

To learn more about the Water Ozonator we invite you to visit the SOTA website:

[www.sota.com](http://www.sota.com)

The website offers Videos, Frequently Asked Questions, *The SOTA Wellness Program Guide*, SOTA News ... and more.

## COMPLETE UNIT INCLUDES

- One (1) Water Ozonator Unit
- One (1) Airstone and Tubing Set
- One (1) Wall Adaptor
- One (1) Product Manual



## DO NOT USE

1. As with all electrical products do not use near water, when driving a car or when operating heavy equipment.

## CAUTIONS

1. Avoid breathing the ozone directly from the Airstone as it may irritate lung tissue. Use in a well-ventilated area, such as under a stove top exhaust fan.
2. Do not operate the unit without the built-in air pump running. If the air pump is not running there will be no bubbles coming from the airstone.
3. While this technology is generally considered safe, there exists potential for rare individual reactions that cannot reasonably be foreseen. Therefore, your use of the SOTA Products constitutes your agreement that you are responsible for your decision to use the technology and that you hold SOTA harmless for any injuries or damage believed to arise from using the SOTA Products.

## SUMMARY OF LIGHTS

GREEN: Indicates the unit is on as well as the timing selected.


## HOW TO USE THE WATER OZONATOR

1. Insert the power plug from the AC-DC Wall Adaptor into the unit and plug the adaptor into an electrical outlet.
2. Connect the silicone tubing to the ozone outlet pipe on the side of the Water Ozonator.

Note: To make it easier to connect, dip the end of the silicone tubing in water. The silicone tubing will then slip on easier.

3. Submerge the Airstone, attached to the silicone tubing, in a glass or stainless steel container of water. Use a glass or stainless steel container as they are ozone resistant.

a. Chilled water holds more ozone but room temperature water is healthier for the



stomach.


- b. It is important to place the water with submerged airstone in a well-ventilated area, as concentrated ozone in air may irritate lung tissue. For example, under a stove-top fan. Place the container of ozonating water well away from the ozone unit.

Note: Ozonating liquids other than water may clog the airstone and will void the warranty.

4. Touch or push the ON/OFF/TIMER button to turn the unit ON. If you have a touch switch, it only works with your bare finger. All the lights will flash in sequence to indicate the unit is ready for use.

- a. The unit starts with the 5 minute timer cycle.
- b. If more than 5 minutes is required, touch or push the ON/OFF/TIMER button – each touch or push moves the timer from 15, to 30, to 60 minutes. A GREEN flashing light indicates which time is set. See page 6 for timing.

5. Check to be sure fine bubbles pass out of the Airstone into the water. If you do not see any bubbles, ensure the silicone tubing is firmly attached to the ozone outlet on the side of the unit. As the unit operates, you should catch the smell of ozone.



6. At the end of a timed session, the unit will beep, all the LED lights will flash, and the air pump will continue to operate for an additional 10 seconds to purge the ozone from the tube. The unit will then turn itself OFF.

Allow water to drain from the tubing after use. This ensures water will not drain back into the unit.

7. Use the freshly ozonated water *immediately* for optimal results. If left for 20 minutes in open air, the ozone dissipates out of the water. You can still experience benefits if you store ozonated water in a glass container with a lid and drink it throughout the day.
8. To turn the unit OFF at any time, hold the ON/OFF/TIMER button for a full two seconds.

9. Turn the unit off and *unplug the wall adaptor* when not in use.

#### Notes:

**Temperature of Water:** Chilled water holds more ozone, however room temperature water is healthier for the stomach.

**Timing:** When the timer is set for 15, 30 or 60 minutes, the lights indicate remaining time. For example, when set for 60 minutes, the GREEN 60 minute LED flashes continuously. As time progresses, the GREEN 30 minutes LED comes on as well to indicate there is 30 minutes or less remaining. As time progresses, the 15 and then 5 minute LEDs will each come on to indicate the time remaining.

**Storage:** Larger quantities of ozonated water can be stored in a glass or stainless steel container with an air-tight lid. The amount of ozone in the water will continue to dissipate, eventually leaving no ozone in the water.

**Charcoal filter:** A charcoal filter inside the unit protects the circuit from the ozone in air. Excess beads of charcoal may fall off the filter and out of the unit. This is normal. Simply discard the beads.

**Pump:** If the built-in air pump stops running, turn the unit off and contact your closest repair depot. See page 7.

#### TYPICAL USE

**Wellness Program:** To use as part of the *SOTA Wellness Program* the Guide is available at: [www.sota.com/wellness](http://www.sota.com/wellness)

#### General Use:

- **Quantity:** Start with 8 ounces (250 ml) per day preferably in the morning. Increase the amount you drink by 8 ounces (250 ml) every second day until you reach 32-64 ounces (1-2 liters) per day. It is best to drink ozonated water on an empty stomach.
- **Length of Use:** We suggest following the SOTA Wellness Program for 6 to 12 months. Being consistent with drinking Ozonated Water is the key to getting results.

#### STERILIZING WATER

The Water Ozonator exceeds the minimum Oxidation Reduction Potential (ORP) of 650 mV required for water sterilization. It does not remove impurities such as heavy metals - a water filtration system is needed for that. The amount of time required to sterilize water depends on the degree of contamination of the water and the water temperature. Colder water holds more ozone.

## WATER DISINFECTION TESTS

Tests by two independent laboratories proved the effectiveness of the ozone generated by a SOTA Water Ozonator in killing the following virulent pathogens:

Escherichia coli (E coli)	Salmonella spp (typhoid fever)
Pseudomonas aeruginosa	Shigella spp
Staphylococcus aureus	Proteus mirabilis
Klebsiella spp	Candida spp

## TIMING TO SATURATE WITH OZONE

Quantity of Water	Timed Setting
4 cups (1 quart or 1 liter) or less	5 minutes
1 gallon or 4 liters	15 minutes
2 gallons or 8 liters	30 minutes
4 gallons or 16 liters	60 minutes

*\*More time may be required to sterilize water.*

## OXIDATION REDUCTION POTENTIAL (ORP)

One cup of chilled distilled water with ice cubes is saturated with ozone within 2 minutes to over 1,000 mV ORP.

## ELECTRICAL SPECIFICATIONS

### POWER REQUIREMENTS

12 Volts DC @ minimum 1.5 Amps, **Tip or Center Positive.**

**Caution:** Exceeding the voltage rating or reverse connection may result in injury or unit failure. This will **void** the warranty.

### OPTIONAL POWER INPUT

To operate the ozone generator from a 12 Volt DC source such as an automobile

battery, or an appropriate solar panel, purchase a Universal Power Cord with **Tip or Center Positive** polarity.

## OUTPUT SPECIFICATIONS

Greater than 200 mg/Hr O<sub>3</sub> @ 1.5 LPM. Measured using an Ozone-in-Air GM Anseros Ozone Analyzer, Model Ozomat GM 6000-RT.

## OZONE GENERATOR CONSTRUCTION

Uses Fused Quartz Glass and High Grade Stainless-Steel ozone chamber. With normal use, the chamber should last several years.

## TROUBLESHOOTING

A Troubleshooting Guide for the Water Ozonator is available at [www.sota.com/manuals](http://www.sota.com/manuals). This Guide is a great tool to check if you are experiencing any issues with your unit.

## COUNTRIES THAT PARTICIPATE IN MANUFACTURING

The manufacturing of the SOTA Products is a global collaboration. The following countries participate in the making of the Water Ozonator (listed in alphabetical order): **Canada, China, Hong Kong, Malaysia, Taiwan and Thailand.**

## REPLACEMENT ACCESSORIES

To replace your accessories, please contact your supplier.

## WARRANTY

The Water O<sub>3</sub>zonator Model WOZ5 is covered by a two (2) year parts and labor warranty on all internally mounted components. Please keep proof of purchase. Warranty is void if the failure is due to abuse or negligence.

## REPAIRS

Please contact your supplier for return instructions. For information about your closest repair depot, contact [repairs@sota.com](mailto:repairs@sota.com) or call 1.250.770.2023 or 1.800.224.0242 (toll-free in Canada & USA).



Made in China. Designed and Engineered in Canada.