

## How to Compare the *Magnetic Pulser* to Other Units

here are a number of Magnetic Pulser units on the market today – some are based on the same technology as the SOTA unit, while others use a different approach. Because of the number of units out there, it would be impossible for us to comment and compare them fairly and accurately to our own unit. We can, however, offer a few guidelines that can be used when you are comparing Magnetic Pulser units.



Any values stated (such as Gauss,

voltage, etc.) should be backed up by scientific testing. The manufacturer should be able to provide you with the name of the testing equipment used and the equipment should be suitable for that purpose. Proper testing equipment is expensive – it is reliable and accurate in the results that it provides. Less expensive equipment may give inaccurate results, which cannot be relied on. For example, the correct Gauss Meter must be used to capture the actual Gauss output.

Many manufacturers use inferior meters that simply do not and cannot accurately measure the fast DC magnetic field output. SOTA uses the F.W. Bell 5080 Tesla Meter. Other low-cost economy Gauss meters like the Tri-Field meter, simply cannot take accurate readings of the output of these types of DC magnetic pulsers.

Over the years SOTA has tested a number of magnetic pulse units made and advertised by several manufacturers – many of the units claimed to have extremely high Gauss outputs. When tested with the F.W. Bell 5080 Tesla Meter all of these units failed to meet the Gauss output they claimed.

For example, one manufacturer claimed their unit output 50,000 Gauss. When tested with the F.W. Bell 5080 Tesla Meter, the actual and true output was only 1,080 Gauss. This is almost 50 times less than what was claimed and advertised.

Another manufacturer claimed their unit was capable of outputting 30,000 Gauss. When



measured with the F.W. Bell 5080 Tesla Meter, the actual and true output was only 800 Gauss. Again, far lower than what was claimed and advertised.

So, why the difference? Likely, it is due to a misunderstanding of how Gauss is measured and calculated. Improper test equipment could be a factor, but more than likely, the manufacturers are getting their Gauss measurements not from testing equipment, but by using a formula that only provides theoretical values. When SOTA used this same formula, it put the Gauss of our unit at greater than 49,950 Gauss – whereas the measured value was actually 7,000 Gauss at the face of the coil. This is why one cannot rely on a formula for electrical specifications – one needs to do real and actual testing with the correct test equipment.

There could also be a misunderstanding of basic electronics and electronic circuitry by many manufacturers. For example, one manufacturer doubled the number of capacitors in their unit and reported that doing so doubled their gauss output. The two capacitors used in the unit were each rated at 350 VDC, 560uF, which when compared to the SOTA unit that has a 450 VDC, 600uF capacitor, it erroneously appears as if the output would be more than the SOTA Magnetic Pulser. When the unit was tested however, it was found that while the unit charged each capacitor to 330 Volts, it was only firing one capacitor at a time. In other words, one capacitor was firing (releasing) its charge while the other capacitor was charging. The capacitors were never firing at the same time. The measured gauss of the unit was 5,090 at the face of the paddle, as compared to 7,000 Gauss at the face of the SOTA paddle.

Most of the units we have tested over the years were sent to us by people who had purchased them and wanted to know the gauss output.

Whenever we come across a unit from another manufacturer whose actual output is different from the advertised output, we get in touch with that manufacturer to let them know our findings. We do not make these findings public. To date, with the exception of one, all manufacturers we have contacted have not changed their advertising nor have they indicated they had independent testing done to verify their advertised numbers.

SOTA offers a testing service for manufacturers to test their units. We use our testing equipment to give accurate, true and unbiased results.

When comparing Magnetic Pulsers, it is important to not only compare the electrical specifications of the units but also to compare any external testing, certifications or testing standards that the units have or have not met.

The SOTA units have been CE certified and are RoHS compliant.

CE is a European standard that ensures a product meets certain regulatory standards set by the European Union. Having CE on the units ensures products are safe to use and do not



output hazardous levels of EMRs (electromagnetic radiation, like cellular phones do).

RoHS is the Restriction of use of Hazardous Substances and is again, a European standard. In order to be RoHS compliant, electronic products must not use any of the following six substances: Cadmium (Cd), hexavalent Chromium (CR VI), Lead (Pb), Mercury (Hg), polybrominated biphenyls (PBB) and polybrominated diphenyl ethers (PBDE).

It is very important to make an informed and intelligent decision before purchasing any equipment. Be willing to ask the manufacturer for the test data. They should have this data readily available and be ready to share it. Unfortunately, what we have seen from our testing experience is that what you think you are buying is not always what you are actually receiving.

• The SOTA units are consumer products designed to be used as part of a Wellness Lifestyle • The SOTA units are not medical devices nor are they intended to diagnose, treat or cure any medical or health condition • The use, safety or effectiveness of the SOTA units has not been approved by any government agency • Please consult a health practitioner for any medical or health condition • Results using the SOTA Products will vary for each person • Please note that all purchases of SOTA Products are deemed to be made in Penticton, BC, Canada •